

WLS DUALCAM1122



Features:

- Aluminium alloy housing
- Wide angle lens
- Camera 1 Build-in IR LED
- Camera 1 audio output
- Camera 2 option 120 dB Real WDR

Camera 1

Item	Specifications
Image Sensor	1/3" CMOS
Picture elements	1280 x 960
Scanning system	Progressive scan RGB CMOS
S/N Ratio	44 dB
Auto gain control	Auto
Electronic shutter	Auto
BLC	Auto
Infrared spectrum	940 nm
Infrared LED	6 LED
Audio	Available
Mirror	Optional
Noise reduction	3D
Dynamic range	83.5 dB
Lens	f 2.5mm Megapixel
Pan (adjusting)	0-50°
Tilt (adjusting)	0-50°
Power supply	9-18V DC
Power consumption	110 mA
Operating temperature	-30 °C to +70 °C

Camera 2

Item	Specifications
Image Sensor	1/3" CMOS
Picture elements	1280 x 960
Scanning system	Progressive scan RGB CMOS
Sensitivity	0.1 Lux / F1.2
S/N Ratio	44 dB
Auto gain control	Auto
Electronic shutter	Auto
BLC	Auto
Mirror	Optional
Noise reduction	3D
Dynamic range	83.5 dB
Lens	f 2.5mm Megapixel
Tilt (adjusting)	0-80°
Power supply	9-18V DC
Power consumption	70 mA
Operating temperature	-30 °C to +70 °C