

WELSYS

Model: WLS2MPIndoor

SPECIFICATIONS

VIDEO	
Image Sensor	1/3" CMOS
Max. Resolution	1920 x 1080p
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	f=4.0mm
Aperture	F=2.15
Iris Control	Fixed Iris
Angular Field of View	83°(H), 43°(V), 100.4°(D)
Pan / Tilt Range	Pan: -175° ~ 175°, Tilt: 0° ~ 70°, Rotate: -90° ~ 90°
Min. Illumination	Color : 0.2 lux @ F2.15 B/W : 0 lux (IR LED ON)
Dynamic Range	100dB
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10000), Anti-Flicker, Slow Shutter (1~1/5, 1/7.5, 1/15)
Day and Night	IR cut filter with auto switch
IR Distance (LEDs)	20 m / 65.6 ft (2 ea)
Image Setting	Configurable Exposure, White Balance, Sharpness
Digital Noise Reduction	Configurable 2DNR/3DNR
Backlight Compensation	On / Off / HSBC
Digital zoom	12x
De-fog	On / Off
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Video Out	-
NETWORK	
Video Compression	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported
Bitrate Control	H.265 - VBR / CBR H.264 - VBR / CBR
Audio Compression	-
Two-way Audio	Full duplex
IP Camera Protocol	ONVIF S
Max. Frame Rate	30ips : 1920 x 1080
Supported Resolution	1920 x 1080, 1280 x 720, 704 x 480, 640 x 360, 352 x 240
Multi-video Streaming	Quadruple Streaming
Network Protocols	Protocol, R TP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP, R TSP/TCP, HTTP, HTTPS, FTP, ,SNTP, SMTP, FEN, mDNS, uPNP
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS, SSL Encryption
Remote Access Client	Off / On
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTRec)	Yes (Up to 10MB)
Edge Storage	-
ALARM AND EVENT	
Trigger Event	Motion Detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (With Image)
ENVIRONMENTAL	
Vandal Proof Casing	IK06
Outdoor Ready	IP65
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting Up at Above 0°C (32°F)
Operating Humidity	0% ~ 90%
ELECTRICAL	
Power Source	PoE (IEEE 802.3af Class 2)
Power Consumption	PoE (IEEE 802.3af Class 2), 4.6W
Approvals	FCC, CE, KC
MECHANICAL	
Dimensions	Ø130mm x 74.3mm (Ø5.12" x 2.93")
Weight	0.21kg (0.46 lb)